



Qualikems

Qualikems Lifesciences Pvt. Ltd.

(Formerly known as Qualikems fine chem Pvt Ltd)

Works : Plot No. 68-69,G.I.D.C Industrial Estate,Nandesari,Vadodara-391340 (Gujarat)

Telefax : 91-265-2841531,2841532,2841534,2841535.

Sales Office : 5531,Basti Harphool singh Sadar Thana Road, Delhi-110006

Tel : +91-11-23618475/23618476,Fax:+91-11-23678476

Email: salesindia@qualikems.com ,www.qualikems.com

SECTION 1: Identification of the substance/mixture and of the company/undertaking

Product identifiers

Product name : **2-Mercapto Ethanol**

CAS-No. : **60-24-2**

Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Laboratory chemicals, Industrial & for professional use only.

Details of the supplier of the safety data sheet

Company : Qualikems Lifesciences Pvt Ltd

Works : Plot No. 68.69,G.I.D.C
Industrial Estate, Nandesari,
Vadodara-391340 (Gujarat)

Emergency telephone number

Emergency Phone # : +91-265-2841531 (9:00am - 6:30 pm) [Office hours]

SECTION 2: Hazards identification

Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

Acute toxicity, Oral (Category 3), H301

Acute toxicity, Inhalation (Category 3), H331

Acute toxicity, Dermal (Category 2), H310

Skin irritation (Category 2), H315

Serious eye damage (Category 1), H318

Skin sensitisation (Category 1), H317

Specific target organ toxicity - repeated exposure, Oral (Category 2), Liver, Heart, H373

Acute aquatic toxicity (Category 1), H400

Chronic aquatic toxicity (Category 1), H410

For the full text of the H-Statements mentioned in this Section, see Section 16.

Classification according to EU Directives 67/548/EEC or 1999/45/EC

T, N Toxic, Dangerous for the environment R23/24/25, R38, R41, R43, R48/22, R50/53

For the full text of the R-phrases mentioned in this Section, see Section 16.

Label elements

Labelling according Regulation (EC) No 1272/2008

Pictogram

Signal word



Hazard statement(s)

H301 + H331

H310

H315

H317

H318

H373

H410

Precautionary statement(s)

P261

P280

P301 + P310 + P330

P302 + P352 + P310

P305 + P351 + P338 + P310

P403 + P233

Supplemental Hazard

Statements

Danger

Toxic if swallowed or if inhaled

Fatal in contact with skin.

Causes skin irritation.

May cause an allergic skin reaction.

Causes serious eye damage.

May cause damage to organs (Liver, Heart) through prolonged or repeated exposure if swallowed.

Very toxic to aquatic life with long lasting effects.

Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.

Wear protective gloves/ protective clothing/ eye protection/ face protection.

IF SWALLOWED: Immediately call a POISON CENTER or doctor/ physician. Rinse mouth.

IF ON SKIN: Wash with plenty of water. Immediately call a POISON CENTER or doctor/ physician.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor/ physician.

Store in a well-ventilated place. Keep container tightly closed.

none

Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Stench.

Stench., Rapidly absorbed through skin.

SECTION 3: Composition/information on ingredients

3.1 Substances

Synonyms : Thioethylene glycol
2-Hydroxyethylmercaptan
BME
β-Mercaptoethanol

Formula : C₂H₆OS
Molecular weight : 78,13 g/mol
CAS-No. : 60-24-2
EC-No. : 200-464-6

Hazardous ingredients according to Regulation (EC) No 1272/2008

Component	Classification	Concentration
2-Mercaptoethanol		
CAS-No.	60-24-2	Acute Tox. 3; Acute Tox. 2;
EC-No.	200-464-6	Skin Irrit. 2; Eye Dam. 1; Skin Sens. 1; STOT RE 2; Aquatic Acute 1; Aquatic Chronic 1; H301 + H331, H310, H315, H317, H318, H373, H410
		<= 100 %

Hazardous ingredients according to Directive 1999/45/EC

Component	Classification	Concentration
-----------	----------------	---------------

2-Mercaptoethanol

CAS-No.

60-24-2

T, N, R23/24/25 - R38 - R41 - <= 100 %

EC-No.

200-464-6

R43 - R48/22 - R50/53

For the full text of the H-Statements and R-Phrases mentioned in this Section, see Section 16

SECTION 4: First aid measures

Description of first aid measures

General advice

Consult a physician. Show this safety data sheet to the doctor in attendance.

If inhaled

If breathed in, move person into fresh air. If not breathing, give artificial respiration. Consult a physician.

In case of skin contact

Wash off with soap and plenty of water. Take victim immediately to hospital. Consult a physician.

In case of eye contact

Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.

If swallowed

Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician.

Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

Indication of any immediate medical attention and special treatment needed

No data available

SECTION 5: Firefighting measures

Extinguishing media Suitable

extinguishing media

Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

Special hazards arising from the substance or mixture

Carbon oxides, Sulphur oxides

Advice for firefighters

Wear self-contained breathing apparatus for firefighting if necessary.

Further information

Use water spray to cool unopened containers.

SECTION 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures

Wear respiratory protection. Avoid breathing vapours, mist or gas. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

For personal protection see section 8.

Environmental precautions

Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Discharge into the environment must be avoided.

Methods and materials for containment and cleaning up

Contain spillage, and then collect with an electrically protected vacuum cleaner or by wet-brushing and place in container for disposal according to local regulations (see section 13). Keep in suitable, closed containers for disposal.

Reference to other sections

For disposal see section 13.

SECTION 7: Handling and storage

Precautions for safe handling

Avoid contact with skin and eyes. Avoid inhalation of vapour or mist.

Keep away from sources of ignition - No smoking. Take measures to prevent the build up of electrostatic charge.

For precautions see section 2.2.

Conditions for safe storage, including any incompatibilities

Store in cool place. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

Recommended storage temperature 2 - 8 °C

Storage class (TRGS 510): Non-combustible, acute toxic Cat. 1 and 2 / very toxic hazardous materials

Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

SECTION 8: Exposure controls/personal protection

Control parameters

Components with workplace control parameters

Exposure controls

Appropriate engineering controls

Avoid contact with skin, eyes and clothing. Wash hands before breaks and immediately after handling the product.

Personal protective equipment

Eye/face protection

Tightly fitting safety goggles. Faceshield (8-inch minimum). Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166 (EU).

Skin protection

Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

Body Protection

Complete suit protecting against chemicals, The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

Respiratory protection

Where risk assessment shows air-purifying respirators are appropriate use a full-face respirator with multi-purpose combination (US) or type ABEK (EN 14387) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

Control of environmental exposure

Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Discharge into the environment must be avoided.

SECTION 9: Physical and chemical properties

Information on basic physical and chemical properties

- | | |
|---------------|--|
| a) Appearance | Form: liquid
Colour: colourlessyellow |
|---------------|--|

b) Odour	Stench.
c) Odour Threshold	No data available
d) pH	4,5 - 6 at 500 g/l at 20 °C
e) Melting point/freezing point	< -49,99 °C
f) Initial boiling point and boiling range	157 °C - lit.
g) Flash point	74 °C - closed cup
h) Evaporation rate	No data available
i) Flammability (solid, gas)	No data available
j) Upper/lower flammability or explosive limits	Upper explosion limit: 18 %(V) Lower explosion limit: 2,3 %(V)
k) Vapour pressure	0,76 hPa at 20 °C 4,67 hPa at 40 °C
l) Vapour density	2,70 - (Air = 1.0)
m) Relative density	1,114 g/cm ³ at 25 °C
n) Water solubility	soluble
o) Partition coefficient: n-octanol/water	log Pow: -0,326 log Pow: -0,056 at 25 °C
p) Auto-ignition temperature	No data available
q) Decomposition temperature	No data available
r) Viscosity	No data available
s) Explosive properties	No data available
t) Oxidizing properties	No data available

Other safety information

Relative vapour density 2,70 - (Air = 1.0)

SECTION 10: Stability and reactivity

Reactivity

No data available

Chemical stability

Stable under recommended storage conditions.

Possibility of hazardous reactions

No data available

Conditions to avoid

Heat, flames and sparks.

Incompatible materials

Metals, Oxidizing agents

Hazardous decomposition products

Other decomposition products - No data available
In the event of fire: see section 5

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

LD50 Oral - Rat - 98 - 162 mg/kg
(OECD Test Guideline 401)

LC50 Inhalation - Rat - 4 h - 2 mg/l

LC50 Inhalation - Rat - 4 h - 625 ppm

LD50 Dermal - Rabbit - 112 mg/kg

Skin corrosion/irritation

Skin - Rabbit

Result: Irritating to skin.
(Draize Test)

Serious eye damage/eye irritation

Eyes - Rabbit

Result: Risk of serious damage to eyes.

Respiratory or skin sensitisation

Maximisation Test (GPMT) - Guinea pig
May cause sensitisation by skin contact.
(OECD Test Guideline 406)

Germ cell mutagenicity

Experiments showed mutagenic effects in cultured bacterial cells.

Carcinogenicity

IARC: No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

Reproductive toxicity

No data available

Specific target organ toxicity - single exposure

No data available

Specific target organ toxicity - repeated exposure

Ingestion - May cause damage to organs through prolonged or repeated exposure. - Liver, Heart

Aspiration hazard

No data available

Additional Information

RTECS: KL5600000

burning sensation, Cough, wheezing, laryngitis, Shortness of breath, Headache, Nausea, Vomiting, Weakness, Unconsciousness, Material is extremely destructive to tissue of the mucous membranes and upper respiratory tract, eyes, and skin., spasm, inflammation and edema of the larynx, spasm, inflammation and edema of the bronchi, pneumonitis, pulmonary edema
To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.

SECTION 12: Ecological information

Toxicity

Toxicity to fish

Toxicity to daphnia and other aquatic invertebrates LC50 - Leuciscus idus (Golden orfe) - 46 - 100 mg/l - 96,0 h
EC50 - Daphnia (water flea) - 0,89 mg/l - 48 h (OECD Test Guideline 202)

Toxicity to algae

Toxicity to bacteria EC50 - Desmodesmus subspicatus (green algae) - 12 mg/l - 72 h
LC50 - Bacteria - 125 mg/l - 17 h

Persistence and degradability

Biodegradability Result: < 30,0 % - Not readily biodegradable.
Result: 6 % - Not readily biodegradable.
aerobic - Exposure time 28 d
Result: < 10 % - Not readily biodegradable.

Biochemical Oxygen Demand (BOD) 105 mg/g

Chemical Oxygen Demand (COD) 1,894 mg/g

Bioaccumulative potential

Does not accumulate in organisms.

Mobility in soil

No data available

Results of PBT and vPvB assessment

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Other adverse effects

Very toxic to aquatic life with long lasting effects.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

This combustible material may be burned in a chemical incinerator equipped with an afterburner and scrubber. Offer surplus and non-recyclable solutions to a licensed disposal company.

Contaminated packaging

Dispose of as unused product.

SECTION 14: Transport information

UN number

ADR/RID: 2966

IMDG: 2966

IATA: 2966

UN proper shipping name

ADR/RID: THIOGLYCOL

IMDG: THIOGLYCOL

IATA: Thioglycol

Transport hazard class(es)

ADR/RID: 6.1

IMDG: 6.1

IATA: 6.1

Packaging group

ADR/RID: II

IMDG: II

IATA: II

Environmental hazards

ADR/RID: yes

IMDG Marine pollutant: yes

IATA: no

Special precautions for user

No data available

SECTION 15: Regulatory information

This safety datasheet complies with the requirements of Regulation (EC) No. 1907/2006.

Safety, health and environmental regulations/legislation specific for the substance or mixture

Chemical Safety Assessment

For this product a chemical safety assessment was not carried out

SECTION 16: Other information

Full text of H-Statements referred to under sections 2 and 3.

Acute Tox.	Acute toxicity
Aquatic Acute	Acute aquatic toxicity
Aquatic Chronic	Chronic aquatic toxicity
Eye Dam.	Serious eye damage
H301	Toxic if swallowed.
H301 + H331	Toxic if swallowed or if inhaled
H310	Fatal in contact with skin.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H331	Toxic if inhaled.
H373	May cause damage to organs through prolonged or repeated exposure if swallowed.
H400	Very toxic to aquatic life.

Full text of R-phrases referred to under sections 2 and 3

N	Dangerous for the environment
T	Toxic
R23/24/25	Toxic by inhalation, in contact with skin and if swallowed.
R38	Irritating to skin.
R41	Risk of serious damage to eyes.
R43	May cause sensitisation by skin contact.
R48/22	Harmful: danger of serious damage to health by prolonged exposure if swallowed.
R50/53	Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Further information

The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. Qualikems Lifesciences Pvt. Ltd and its Affiliates shall not be held liable for any damage resulting from handling or from contact with the above product. See www.qualikems.com for additional terms and conditions of sale.