



Qualikems Lifesciences Pvt. Ltd.

(Formerly known as Qualikems fine chem Pvt Ltd)

Works : Plot No. 68-69,G.I.D.C Industrial Estate,Nandesari,Vadodara-391340 (Gujarat)

Telefax : 91-265-2841531,2841532,2841534,2841535.

Sales Office : 5531,Basti Harphool singh Sadar Thana Road, Delhi-110006

Tel : +91-11-23618475/23618476,Fax:+91-11-23678476

Email: salesindia@qualikems.com ,www.qualikems.com

SECTION 1: Identification of the substance/mixture and of the company/undertaking

Product identifiers

Product name : Petroleum Ether 40-60 °C

CAS-No. : 8032-32-4

Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Laboratory chemicals, Industrial & for professional use only.

Details of the supplier of the safety data sheet

Company : Qualikems Lifesciences Pvt Ltd

Works : Plot No. 68.69,G.I.D.C
Industrial Estate, Nandesari,
Vadodara-391340 (Gujarat)

Emergency telephone number

Emergency Phone # : +91-265-2841531 (9:00am - 6:30 pm) [Office hours]

SECTION 2: Hazards identification

Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

Flammable liquids (Category 2), H225

Specific target organ toxicity - single exposure (Category 3), Central nervous system, H336

Aspiration hazard (Category 1), H304

Chronic aquatic toxicity (Category 2), H411

For the full text of the H-Statements mentioned in this Section, see Section 16.

Label elements

Labelling according Regulation (EC) No 1272/2008

Pictogram



Signal word

Danger

Hazard statement(s)

H225

Highly flammable liquid and vapour.

H304

May be fatal if swallowed and enters airways.

H336

May cause drowsiness or dizziness.

H411

Toxic to aquatic life with long lasting effects.

Precautionary statement(s)	
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P273	Avoid release to the environment.
P301 + P310	IF SWALLOWED: Immediately call a POISON CENTER/doctor.
P331	Do NOT induce vomiting.
P391	Collect spillage.
P403 + P235	Store in a well-ventilated place. Keep cool.
Supplemental Hazard information (EU)	
EUH066	Repeated exposure may cause skin dryness or cracking.

Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher. Repeated exposure may cause skin dryness or cracking.

SECTION 3: Composition/information on ingredients

3.1 Substances

Synonyms : Petroleum benzin

CAS-No. : 8032-32-4

EC-No. : 309-852-0

Hazardous ingredients according to Regulation (EC) No 1272/2008

Component	Classification	Concentration
Hydrocarbon mixture C5-C Aliphates		
CAS-No. 8032-32-4	Flam. Liq. 2; STOT SE 3; Asp.	<= 100 %
EC-No. 309-852-0	Tox. 1; Aquatic Chronic 2; H225, H336, H304, H411	
n-Hexane		
CAS-No. 110-54-3	Flam. Liq. 2; Skin Irrit. 2; Repr.	>= 1 - < 2.5 %
EC-No. 203-777-6	2; STOT SE 3; STOT RE 2; Asp. Tox. 1; Aquatic Chronic	
Index-No. 601-037-00-0	2; H225, H315, H361f, H336, H373, H304, H411 Concentration limits: >= 5 %: STOT RE 2, H373;	

For the full text of the H-Statements mentioned in this Section, see Section 16.

SECTION 4: First aid measures

Description of first aid measures

General advice

Consult a physician. Show this safety data sheet to the doctor in attendance.

If inhaled

If breathed in, move person into fresh air. If not breathing, give artificial respiration. Consult a physician.

In case of skin contact

Wash off with soap and plenty of water. Consult a physician.

In case of eye contact

Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.

If swallowed

Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician.

Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

Indication of any immediate medical attention and special treatment needed

No data available

SECTION 5: Firefighting measures**Extinguishing media Suitable****extinguishing media**

Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

Special hazards arising from the substance or mixture

Carbon oxides

Flash back possible over considerable distance., Container explosion may occur under fire conditions.

Advice for firefighters

Wear self-contained breathing apparatus for firefighting if necessary.

Further information

Use water spray to cool unopened containers.

SECTION 6: Accidental release measures**Personal precautions, protective equipment and emergency procedures**

Use personal protective equipment. Avoid breathing vapours, mist or gas. Ensure adequate ventilation.

Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

For personal protection see section 8.

Environmental precautions

Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Discharge into the environment must be avoided.

Methods and materials for containment and cleaning up

Contain spillage, and then collect with an electrically protected vacuum cleaner or by wet-brushing and place in container for disposal according to local regulations (see section 13).

Reference to other sections

For disposal see section 13.

SECTION 7: Handling and storage**Precautions for safe handling**

Avoid contact with skin and eyes. Avoid inhalation of vapour or mist.

Keep away from sources of ignition - No smoking. Take measures to prevent the build up of electrostatic charge.

For precautions see section 2.2.

Conditions for safe storage, including any incompatibilities

Store in cool place. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

Storage class (TRGS 510): Flammable liquids

Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

SECTION 8: Exposure controls/personal protection**Control parameters****Exposure controls****Appropriate engineering controls**

Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.

Personal protective equipment

Eye/face protection

Face shield and safety glasses Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

Skin protection

Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

Body Protection

Complete suit protecting against chemicals, Flame retardant antistatic protective clothing., The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

Respiratory protection

Where risk assessment shows air-purifying respirators are appropriate use (US) or type AXBEK (EN 14387) respirator cartridges as a backup to engine protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

Control of environmental exposure

Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Discharge into the environment must be avoided.

SECTION 9: Physical and chemical properties

Information on basic physical and chemical properties

a) Appearance	Form: liquid, clear Colour: colourless
b) Odour	No data available
c) Odour Threshold	No data available
d) pH	No data available
e) Melting point/freezing point	No data available
f) Initial boiling point and boiling range	40 - 60 °C
g) Flash point	-39.99 °C - closed cup
h) Evaporation rate	No data available
i) Flammability (solid, gas)	No data available
j) Upper/lower flammability or explosive limits	No data available
k) Vapour pressure	No data available
l) Vapour density	No data available
m) Relative density	0.642 - 0.656 g/mL at 20 °C
n) Water solubility	No data available
o) Partition coefficient: n-octanol/water	No data available
p) Auto-ignition temperature	No data available
q) Decomposition temperature	No data available

- r) Viscosity No data available
s) Explosive properties In use may form flammable/explosive vapour-air mixture.
t) Oxidizing properties No data available

Other safety information

No data available

SECTION 10: Stability and reactivity

Reactivity

No data available

Chemical stability

Stable under recommended storage conditions.

Possibility of hazardous reactions

No data available

Conditions to avoid

Heat, flames and sparks.

Incompatible materials

Strong oxidizing agents

Hazardous decomposition products

Other decomposition products - No data available

Hazardous decomposition products formed under fire conditions. - Carbon oxides

In the event of fire: see section 5

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

No data available Hydrocarbon mixture C5-C8 Aliphates

Skin corrosion/irritation

Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin resulting in desiccation of the skin. (Hydrocarbon mixture C5-C8 Aliphates)

Serious eye damage/eye irritation

Eyes - Rabbit (Hydrocarbon mixture C5-C8 Aliphates)

Result: Mild eye irritation

Respiratory or skin sensitisation

No data available (Hydrocarbon mixture C5-C8 Aliphates)

Germ cell mutagenicity

No data available (Hydrocarbon mixture C5-C8 Aliphates)

Carcinogenicity

IARC: No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

Reproductive toxicity

No data available (Hydrocarbon mixture C5-C8 Aliphates)

Specific target organ toxicity - single exposure

May cause drowsiness or dizziness. (Hydrocarbon mixture C5-C8 Aliphates)

Specific target organ toxicity - repeated exposure

No data available

Aspiration hazard

May be fatal if swallowed and enters airways. (Hydrocarbon mixture C5-C8 Aliphates)

Additional Information

RTECS: Not available

SECTION 12: Ecological information

Toxicity

Toxicity to fish LC50 - Fish - 1 - 10 mg/l - 96 h(Hydrocarbon mixture C5-C8 Aliphates)

Persistence and degradability

No data available

Bioaccumulative potential

Due to the distribution coefficient n-octanol/water, accumulation in organisms is possible.

Mobility in soil

No data available(Hydrocarbon mixture C5-C8 Aliphates)

Results of PBT and vPvB assessment

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Other adverse effects

Toxic to aquatic life with long lasting effects.

No data available

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

Burn in a chemical incinerator equipped with an afterburner and scrubber b highly flammable.
Offer surplus and non-recyclable solutions to a licensed disposal company.

Contaminated packaging

Dispose of as unused product.

SECTION 14: Transport information

UN number

ADR/RID: 1268

IMDG: 1268

IATA: 1268

UN proper shipping name

ADR/RID: PETROLEUM DISTILLATES, N.O.S.

IMDG: PETROLEUM DISTILLATES, N.O.S. (Hydrocarbon mixture C5-C8 Aliphates)

IATA: Petroleum distillates, n.o.s.

Transport hazard class(es)

ADR/RID: 3

IMDG: 3

IATA: 3

Packaging group

ADR/RID: II

IMDG: II

IATA: II

Environmental hazards

ADR/RID: no

IMDG Marine pollutant: no

IATA: no

Special precautions for user

No data available

SECTION 15: Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture

This safety datasheet complies with the requirements of Regulation (EC) No. 1907/2006.

Chemical safety assessment

For this product a chemical safety assessment was not carried out

SECTION 16: Other information

Full text of H-Statements referred to under sections 2 and 3.

EUH066	Repeated exposure may cause skin dryness or cracking.
H225	Highly flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H336	May cause drowsiness or dizziness.
H361f	Suspected of damaging fertility.
H373	May cause damage to organs through prolonged or repeated exposure.
H411	Toxic to aquatic life with long lasting effects.

Further information

The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. Qualikems Lifesciences Pvt. Ltd and its Affiliates shall not be held liable for any damage resulting from handling or from contact with the above product. See www.qualikems.com for additional terms and conditions of sale.