



Qualikems Lifesciences Pvt. Ltd.

(Formerly known as Qualikems fine chem Pvt Ltd)

Works : Plot No. 68-69,G.I.D.C Industrial Estate,Nandesari,Vadodara-391340 (Gujarat)

Telefax : 91-265-2841531,2841532,2841534,2841535.

Sales Office : 5531,Basti Harphool singh Sadar Thana Road, Delhi-110006

Tel : +91-11-23618475/23618476,Fax:+91-11-23678476

Email: salesindia@qualikems.com ,www.qualikems.com

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifiers

Product name : **Iso Butanol**

CAS-No. : **78-83-1**

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Laboratory chemicals, Industrial & for professional use only.

1.3 Details of the supplier of the safety data sheet

Company : Qualikems Lifesciences Pvt Ltd

Works : Plot No. 68.69,G.I.D.C
Industrial Estate, Nandesari,
Vadodara-391340 (Gujarat)

Emergency telephone number

Emergency Phone # : +91-265-2841531 (9:00am - 6:30 pm) [Office hours]

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

Flammable liquids (Category 3), H226

Skin irritation (Category 2), H315

Serious eye damage (Category 1), H318

Specific target organ toxicity - single exposure (Category 3), Central nervous system, H336

Specific target organ toxicity - single exposure (Category 3), Respiratory system, H335

For the full text of the H-Statements mentioned in this Section, see Section 16.

2.2 Label elements

Labelling according Regulation (EC) No 1272/2008

Pictogram



Signal word

Danger

Hazard statement(s)

H226

Flammable liquid and vapour.

H315

Causes skin irritation.

H318	Causes serious eye damage.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
Precautionary statement(s)	
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P280	Wear eye protection/ face protection.
P304 + P340 + P312	IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell.
P305 + P351 + P338 + P310	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/doctor.
P403 + P235	Store in a well-ventilated place. Keep cool.
Supplemental Hazard Statements	none

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.1 Substances

Synonyms	:	Isobutanol Isobutyl alcohol
Formula	:	C ₄ H ₁₀ O
Molecular weight	:	74.12 g/mol
CAS-No.	:	78-83-1
EC-No.	:	201-148-0
Index-No.	:	603-108-00-1

Hazardous ingredients according to Regulation (EC) No 1272/2008

Component		Classification	Concentration
iso-Butanol			
CAS-No.	78-83-1	Flam. Liq. 3; Skin Irrit. 2; Eye	<= 100 %
EC-No.	201-148-0	Dam. 1; STOT SE 3; H226,	
Index-No.	603-108-00-1	H315, H318, H336, H335	

For the full text of the H-Statements mentioned in this Section, see Section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice

Consult a physician. Show this safety data sheet to the doctor in attendance.

If inhaled

If breathed in, move person into fresh air. If not breathing, give artificial respiration. Consult a physician.

In case of skin contact

Wash off with soap and plenty of water. Consult a physician.

In case of eye contact

Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.

If swallowed

Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician.

4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

4.3 Indication of any immediate medical attention and special treatment needed

No data available

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

5.2 Special hazards arising from the substance or mixture

Carbon oxides

5.3 Advice for firefighters

Wear self-contained breathing apparatus for firefighting if necessary.

5.4 Further information

Use water spray to cool unopened containers.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Use personal protective equipment. Avoid breathing vapours, mist or gas. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas. For personal protection see section 8.

6.2 Environmental precautions

Prevent further leakage or spillage if safe to do so. Do not let product enter drains.

6.3 Methods and materials for containment and cleaning up

Contain spillage, and then collect with an electrically protected vacuum cleaner or by wet-brushing and place in container for disposal according to local regulations (see section 13).

6.4 Reference to other sections

For disposal see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Avoid contact with skin and eyes. Avoid inhalation of vapour or mist. Keep away from sources of ignition - No smoking. Take measures to prevent the build up of electrostatic charge. For precautions see section 2.2.

7.2 Conditions for safe storage, including any incompatibilities

Store in cool place. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Storage class (TRGS 510): Flammable liquids

7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

8.2 Exposure controls

Appropriate engineering controls

Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.

Personal protective equipment

Eye/face protection

Tightly fitting safety goggles. Faceshield (8-inch minimum). Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

Skin protection

Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

Body Protection

Complete suit protecting against chemicals, Flame retardant antistatic protective clothing., The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

Respiratory protection

Where risk assessment shows air-purifying respirators are appropriate use (US) or type ABEK (EN 14387) respirator cartridges as a backup to enginee protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

Control of environmental exposure

Prevent further leakage or spillage if safe to do so. Do not let product enter drains.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

a) Appearance	Form: liquid Colour: colourless, clear
b) Odour	alcohol-like
c) Odour Threshold	No data available
d) pH	No data available
e) Melting point/freezing point	Melting point/range: -108 °C - lit.
f) Initial boiling point and boiling range	108 °C - lit.
g) Flash point	28 °C - closed cup
h) Evaporation rate	0.6
i) Flammability (solid, gas)	No data available
j) Upper/lower flammability or explosive limits	Upper explosion limit: 10.6 %(V) Lower explosion limit: 1.7 %(V)
k) Vapour pressure	8 hPa at 20 °C
l) Vapour density	2.55
m) Relative density	0.803 g/mL at 25 °C
n) Water solubility	70 g/l at 20 °C - OECD Test Guideline 105 - completely miscible

- | | |
|---|------------------------------------|
| o) Partition coefficient: n-octanol/water | log Pow: 1 at 25 °C |
| p) Auto-ignition temperature | 427 °C |
| q) Decomposition temperature | No data available |
| r) Viscosity | 4.00 mm ² /s at 20 °C - |
| s) Explosive properties | No data available |
| t) Oxidizing properties | No data available |

9.2 Other safety information

- | | |
|-------------------------|--------------------|
| Surface tension | 69.7 mN/m at 20 °C |
| Relative vapour density | 2.55 |

SECTION 10: Stability and reactivity

10.1 Reactivity

No data available

10.2 Chemical stability

Stable under recommended storage conditions.

10.3 Possibility of hazardous reactions

No data available

10.4 Conditions to avoid

Heat, flames and sparks.

10.5 Incompatible materials

Strong oxidizing agents, Acid chlorides, Acid anhydrides
Strong oxidizing agents, Acid chlorides, Acid anhydrides

10.6 Hazardous decomposition products

Hazardous decomposition products formed under fire conditions. - Carbon oxides

Other decomposition products - No data available

In the event of fire: see section 5

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

LD50 Oral - Rat - female - 3,350 mg/kg(iso-Butanol)

(OECD Test Guideline 401)

LC50 Inhalation - Rat - male and female - 4 h - 24.6 mg/l(iso-Butanol)

LD50 Dermal - Rabbit - female - 2,460 mg/kg(iso-Butanol)

(OECD Test Guideline 402)

LD50 Intraperitoneal - Rat - 720 mg/kg(iso-Butanol)

Skin corrosion/irritation Skin

- Rabbit(iso-Butanol) Result:

Irritating to skin. - 24 h

Serious eye damage/eye irritation

Eyes - Rabbit(iso-Butanol)

Result: Risk of serious damage to eyes. - 24 h

(OECD Test Guideline 405)

Respiratory or skin sensitisation

No data available(iso-Butanol)

Germ cell mutagenicity

Hamster(iso-Butanol)

fibroblast

Result: negative

OECD Test Guideline 474(iso-Butanol)

Mouse - male and female

Result: negative

Carcinogenicity

IARC: No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

Reproductive toxicity

Specific target organ toxicity - single exposure

May cause respiratory irritation. - Respiratory Tract(iso-Butanol)

May cause drowsiness or dizziness. - Central nervous system(iso-Butanol)

Specific target organ toxicity - repeated exposure

No data available

Aspiration hazard

No data available(iso-Butanol)

Additional Information

Repeated dose toxicity - Rat - male and female - inhalation (vapour)(iso-Butanol)

RTECS: NP9625000

Cough, Shortness of breath, Headache, Nausea, Vomiting, Central nervous system depression, To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.(iso-Butanol)

SECTION 12: Ecological information

12.1 Toxicity

Toxicity to fish flow-through test LC50 - Pimephales promelas (fathead minnow) - 1,430 mg/l - 96 h(iso-Butanol)

Toxicity to daphnia and other aquatic invertebrates static test EC50 - Daphnia pulex (Water flea) - 1,100 mg/l - 48 h(iso-Butanol)

Toxicity to algae static test EC50 - Pseudokirchneriella subcapitata - 1,799 mg/l - 72 h(iso-Butanol)
(OECD Test Guideline 201)

Toxicity to bacteria Growth inhibition IC50 - Sludge Treatment - > 1,000 mg/l - 16 h(iso-Butanol)

12.2 Persistence and degradability

Biodegradability aerobic - Exposure time 28 d(iso-Butanol)
Result: 70 - 80 % - Readily biodegradable
(OECD Test Guideline 301D)

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available(iso-Butanol)

12.5 Results of PBT and vPvB assessment

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6 Other adverse effects

No data available

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

Burn in a chemical incinerator equipped with an afterburner and scrubber b highly flammable.
Offer surplus and non-recyclable solutions to a licensed disposal company.

Contaminated packaging

Dispose of as unused product.

SECTION 14: Transport information

14.1 UN number

ADR/RID: 1212

IMDG: 1212

IATA: 1212

14.2 UN proper shipping name

ADR/RID: ISOBUTANOL

IMDG: ISOBUTANOL

IATA: ISOBUTANOL

14.3 Transport hazard class(es)

ADR/RID: 3

IMDG: 3

IATA: 3

14.4 Packaging group

ADR/RID: III

IMDG: III

IATA: III

14.5 Environmental hazards

ADR/RID: no

IMDG Marine pollutant: no

IATA: no

14.6 Special precautions for user

No data available

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

This safety datasheet complies with the requirements of Regulation (EC) No. 1907/2006.

15.2 Chemical safety assessment

For this product a chemical safety assessment was not carried out

SECTION 16: Other information

Full text of H-Statements referred to under sections 2 and 3.

H226	Flammable liquid and vapour.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.

Further information

The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. Qualikems Lifesciences Pvt. Ltd and its Affiliates shall not be held liable for any damage resulting from handling or from contact with the above product. See www.qualikems.com for additional terms and conditions of sale.