



Qualikems Lifesciences Pvt. Ltd.

(Formerly known as Qualikems fine chem Pvt Ltd)

Works : Plot No. 68-69,G.I.D.C Industrial Estate,Nandesari,Vadodara-391340 (Gujarat)

Telefax : 91-265-2841531,2841532,2841534,2841535.

Sales Office : 5531,Basti Harphool singh Sadar Thana Road, Delhi-110006

Tel : +91-11-23618475/23618476,Fax:+91-11-23678476

Email: salesindia@qualikems.com ,www.qualikems.com

SECTION 1: Identification of the substance/mixture and of the company/undertaking

Product identifiers

Product name : **n-Butyl Acetate**

CAS-No. : **123-86-4**

2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Laboratory chemicals, Industrial & for professional use only.

Details of the supplier of the safety data sheet

Company : Qualikems Lifesciences Pvt Ltd

Works : Plot No. 68.69,G.I.D.C
Industrial Estate, Nandesari,
Vadodara-391340 (Gujarat)

Emergency telephone number

Emergency Phone # : +91-265-2841531 (9:00am - 6:30 pm) [Office hours]

SECTION 2: Hazards identification

1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

Flammable liquids (Category 3), H226

Specific target organ toxicity - single exposure (Category 3), Central nervous system, H336

For the full text of the H-Statements mentioned in this Section, see Section 16.

Label elements

Labelling according Regulation (EC) No 1272/2008

Pictogram



Signal word

Warning

Hazard statement(s)

H226

H336

Flammable liquid and vapour.

May cause drowsiness or dizziness.

Precautionary statement(s)
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P370 + P378 In case of fire: Use dry powder or dry sand to extinguish.
Supplemental Hazard information (EU)
EUH066 Repeated exposure may cause skin dryness or cracking.

Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.1 Substances

Synonyms : Butyl acetate
Formula : C₆H₁₂O₂
Molecular weight : 116,16 g/mol
CAS-No. : 123-86-4
EC-No. : 204-658-1
Index-No. : 607-025-00-1

No components need to be disclosed according to the applicable regulations.

For the full text of the H-Statements mentioned in this Section, see Section 16.

SECTION 4: First aid measures

Description of first aid measures

General advice

Consult a physician. Show this safety data sheet to the doctor in attendance.

If inhaled

If breathed in, move person into fresh air. If not breathing, give artificial respiration. Consult a physician.

In case of skin contact

Wash off with soap and plenty of water. Consult a physician.

In case of eye contact

Flush eyes with water as a precaution.

If swallowed

Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician.

Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

Indication of any immediate medical attention and special treatment needed

No data available

SECTION 5: Fire fighting measures

Extinguishing media

Suitable extinguishing media

Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

2 Special hazards arising from the substance or mixture

Carbon oxides

- 3 Advice for firefighters**
Wear self-contained breathing apparatus for firefighting if necessary.

Further information

Use water spray to cool unopened containers.

SECTION 6: Accidental release measures

1 Personal precautions, protective equipment and emergency procedures

Use personal protective equipment. Avoid breathing vapours, mist or gas. Ensure adequate ventilation. Remove all sources of ignition. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas. For personal protection see section 8.

Environmental precautions

Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Discharge into the environment must be avoided.

Methods and materials for containment and cleaning up

Contain spillage, and then collect with an electrically protected vacuum cleaner or by wet-brushing and place in container for disposal according to local regulations (see section 13).

Reference to other sections

For disposal see section 13.

SECTION 7: Handling and storage

1 Precautions for safe handling

Avoid inhalation of vapour or mist.

Keep away from sources of ignition - No smoking. Take measures to prevent the build up of electrostatic charge.

For precautions see section 2.2.

2 Conditions for safe storage, including any incompatibilities

Store in cool place. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

Storage class (TRGS 510): Flammable liquids

3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

SECTION 8: Exposure controls/personal protection

1 Control parameters

Components with workplace control parameters

2 Exposure controls

Appropriate engineering controls

Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.

Personal protective equipment

Eye/face protection

Face shield and safety glasses Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

Skin protection

Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

Body Protection

Impervious clothing, Flame retardant antistatic protective clothing., The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

Respiratory protection

Where risk assessment shows air-purifying respirators are appropriate use a full-face respirator with multi-purpose combination (US) or type ABEK (EN 14387) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

Control of environmental exposure

Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Discharge into the environment must be avoided.

SECTION 9: Physical and chemical properties

1 Information on basic physical and chemical properties

- | | |
|---|--|
| a) Appearance | Form: liquid
Colour: colourless |
| b) Odour | like fruit |
| c) Odour Threshold | No data available |
| d) pH | 6,2 at ca.5 g/l at 20 °C |
| e) Melting point/freezing point | Melting point/range: -78 °C - lit. |
| f) Initial boiling point and boiling range | 124 - 126 °C - lit. |
| g) Flash point | 23 °C - closed cup |
| h) Evaporation rate | No data available |
| i) Flammability (solid, gas) | No data available |
| j) Upper/lower flammability or explosive limits | Upper explosion limit: 7,6 %(V)
Lower explosion limit: 1,7 %(V) |
| k) Vapour pressure | 20 hPa at 25 °C |
| l) Vapour density | 4,01 - (Air = 1.0) |
| m) Relative density | 0,878-0.881 g/cm ³ at 20°C |
| n) Water solubility | No data available |
| o) Partition coefficient: n- log Pow: | 2,3 at 25 °C
octanol/water |
| p) Auto-ignition temperature | 415 °C at 1.013 hPa |
| q) Decomposition temperature | No data available |
| r) Viscosity | |
| s) Explosive properties | 0,83 mm ² /s at 20 °C - |
| t) Oxidizing properties | No data available |
| | No data available |

Other safety information

- | | |
|-------------------------|--|
| Surface tension | |
| Relative vapour density | 61,3 mN/m at 20 °C
4,01 - (Air = 1.0) |

SECTION 10: Stability and reactivity

.1 Reactivity

No data available

Chemical stability

Stable under recommended storage conditions.

Possibility of hazardous reactions

No data available

.4 Conditions to avoid

Heat, flames and sparks.

.5 Incompatible materials

Strong oxidizing agents, Strong reducing agents, Strong bases

Hazardous decomposition products

Other decomposition products - No data available

In the event of fire: see section 5

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

LD50 Oral - Rat - female - 10.760 mg/kg
(OECD Test Guideline 423)

LC50 Inhalation - Rat - male and female - 4 h - > 21 mg/l
(OECD Test Guideline 403)

LD50 Dermal - Rabbit - male and female - > 14.112 mg/kg
(OECD Test Guideline 402)

Skin corrosion/irritation

Skin - Rabbit

Result: No skin irritation - 4 h
(OECD Test Guideline 404)

Serious eye damage/eye irritation

Eyes - Rabbit

Result: No eye irritation
(OECD Test Guideline 405)

Respiratory or skin sensitisation

No data available

Germ cell mutagenicity

Ames test

S. typhimurium

Result: negative

Carcinogenicity

This product is or contains a component that is not classifiable as to its carcinogenicity based on its IARC, ACGIH, NTP, or EPA classification.

IARC: No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

Reproductive toxicity

Developmental Toxicity - Rat - Inhalation

No adverse effect has been observed in chronic toxicity tests.

Specific target organ toxicity - single exposure

May cause drowsiness or dizziness. - Central nervous system

Specific target organ toxicity - repeated exposure

No data available

Aspiration hazard

No data available

Additional Information

Repeated dose toxicity
RTECS: AF7350000
Rat - male and female - inhalation (vapour) - NOAEL : 2,4 mg/l

Drowsiness, To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.

SECTION 12: Ecological information**12.1 Toxicity**

Toxicity to fish flow-through test LC50 - Pimephales promelas (fathead minnow) - 18 mg/l - 96 h
(OECD Test Guideline 203)

Toxicity to daphnia and other aquatic invertebrates static test EC50 - Daphnia (water flea) - 44 mg/l - 48 h

Toxicity to algae static test EC50 - Desmodesmus subspicatus (Scenedesmus subspicatus) - 674,7 mg/l - 72 h

Persistence and degradability

Biodegradability aerobic - Exposure time 28 d
Result: 83 % - Readily biodegradable
(OECD Test Guideline 301D)

Bioaccumulative potential

No data available

4 Mobility in soil

No data available

Results of PBT and vPvB assessment

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Other adverse effects

Harmful to aquatic life.

SECTION 13: Disposal considerations**13.1 Waste treatment methods****Product**

Burn in a chemical incinerator equipped with an afterburner and scrubber but exert extra care in igniting as this material is highly flammable. Offer surplus and non-recyclable solutions to a licensed disposal company.

Container packaging

Dispose of as unused product.

SECTION 14: Transport information

.1 UN number

ADR/RID: 1123

IMDG: 1123

IATA: 1123

UN proper shipping name ADR/RID:

BUTYL ACETATES

IMDG: BUTYL ACETATES

IATA: Butyl acetates

.3 Transport hazard class(es)

ADR/RID: 3

IMDG: 3

IATA: 3

.4 Packaging group

ADR/RID: III

IMDG: III

IATA: III

Environmental hazards

ADR/RID: no

IMDG Marine pollutant: no

IATA: no

Special precautions for user

No data available

SECTION 15: Regulatory information

This safety datasheet complies with the requirements of Regulation (EC) No. 453/2010.

Safety, health and environmental regulations/legislation specific for the substance or mixture

No data available

Chemical Safety Assessment

For this product a chemical safety assessment was not carried out

SECTION 16: Other information

Full text of H-Statements referred to under sections 2 and 3.

H314 Repeated exposure may cause skin dryness or cracking.

H226 Flammable liquid and vapour.

H336 May cause drowsiness or dizziness.

Further information

The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. Qualikems Lifesciences Pvt. Ltd and its Affiliates shall not be held liable for any damage resulting from handling or from contact with the above product. See www.qualikems.com for additional terms and conditions of sale.